University of Glasgow

Security and Wrap-up

Networked Systems 3
Lecture 16

Lecture Outline

- Security considerations
  - Traffic monitoring, confidentiality and authentication
  - Validating input data
  - Buffer overflow attacks
- Wrap-up

Traffic Monitoring


- Possible to snoop on traffic on any network link
  - Wireless links – simply listen
  - Wired links – switches can be configured to forward a copy of all traffic to a particular link, for monitoring
- Ability to monitor traffic a legal requirement in many countries, for legal reasons
  - e.g., to enable authorised wiretaps by the police
  - Can also be exploited for malicious purposes

Confidentiality

- Must encrypt data to achieve confidentiality
- Two basic approaches
  - Symmetric cryptography
    - Advanced Encryption Standard (AES a.k.a. Rijndael), Triple-DES
    - Data Encryption Standard (DES) – broken; subject to brute-force attacks
  - Public key cryptography
    - The Diffie-Hellman algorithm
    - The Rivest-Shamir-Adleman (RSA) algorithm
  - Complex mathematics – will not attempt to describe


Symmetric Cryptography

- Function converts plain text into cipher-text
  - Fast – suitable for bulk encryption
  - Cipher-text is binary data, and may need base64 encoding
- Conversation is protected by a secret key
  - The same key is used to encrypt as is used to decrypt
  - Key must be kept secret, else security lost – a problem: how to distribute the key?



Public Key Cryptography

- Key split into two parts:
  - Public key – is widely distributed
  - Private key – must be kept secret
- Encrypt using public key → private key is needed to decrypt
  - Public keys are published in a well known directory → solves the key distribution problem
  - Problem: *very* slow to encrypt and decrypt



Hybrid Cryptography

- Use combination of public-key and symmetric cryptography for security and performance
  - Generate a random, ephemeral, *session* key that can be used with symmetric cryptography
  - Use a public-key system to securely distribute this session key – relatively fast, since session key is small
  - Encrypt the data using symmetric cryptography, keyed by the session key
  - Examples: PGP for email, SSL for web pages

Authentication

- Encryption can ensure confidentiality – but how to tell if a message has been tampered with?
  - Use combination of a *cryptographic hash* and public key cryptography to produce a *digital signature*
  - Gives some confidence that there is no *man-in-the-middle attack* in progress
- Can also be used to prove origin of data

Cryptographic Hash Functions

- Generate a fixed length (e.g., 160 bit) hash code of an arbitrary length input value
  - Should not be feasible to derive input value from hash
  - Should not be feasible to generate a message with the same hash as another
- Examples: MD5 and SHA-1
  - *Note: weaknesses found in both – care required!*

MD5(“It was a bright cold day in April, and the clocks were striking thirteen”) = 2c794fa2698f4b1bc5aa4e290abdf3a5

Digital Signature Algorithms

- Generating a digital signature:
  - Generate a cryptographic hash of the data
  - Encrypt the hash with your *private key* to give a *digital signature*
- Verifying a digital signature:
  - Re-calculate the cryptographic hash of the data
  - Decrypt the signature using the public key, compare with the calculated hash value → should match


Existing Secure Protocols

- Wide range of existing security protocols give confidentiality and authentication:
  - IPsec
  - Transport Layer Security (TLS)
    - An enhancement to the Secure Sockets Layer (SSL)
  - Datagram TLS
  - Secure shell (ssh)
- Use them – don't try to invent your own!

Validating Input Data

- Networked applications fundamentally dealing with data supplied by un-trusted third parties
  - Data read from the network may not conform to the protocol specification
  - Due to ignorance and/or bugs
  - Due to malice, and a desire to disrupt services
- Must carefully validate all data before use

Malicious User Input



http://xkcd.com/327/

- Beware escape characters in user-supplied data!
- Must sanitise all user-supplied data before use
  - Stop malicious users including control characters that might disrupt operation of any scripting language inside your application

Buffer Overflow Attacks

- The C programming language doesn't check array bounds
  - Responsibility of the programmer to ensure bounds are not violated
  - Easy to get wrong – typically results in a "core dump"
  - What actually happens here?

Function Calls and the Stack

```
// overflow.c
#include <string.h>
#include <stdio.h>

static void
foo(char *src)
{
        char dst[12];

        strcpy(dst, src);
}

int
main(int argc, char *argv[])
{
        char hello[] = "Hello, world\n";

        foo(argv[1]);
        printf("%s", hello);
        return 0;
}
```

```
$ gcc overflow.c  -o overflow
$ ./overflow 123456789012
Hello, world
$ ./overflow 1234567890123
Abort trap (core dumped)
$
```

What happens when `argv[1]` is longer than 12 bytes?

Function Calls and the Stack


```
// overflow.c
#include <string.h>
#include <stdio.h>

static void
foo(char *src)
{
        char dst[12];

        strcpy(dst, src);
}

int
main(int argc, char *argv[])
{
        char hello[] = "Hello, world\n";


        foo(argv[1]);
        printf("%s", hello);
        return 0;
}
```



Example of call stack within the call to the function `foo()`

Function Calls and the Stack

- The `strcpy()` call doesn't check array bounds
- Overwrites the function return address on stack, along with the following memory locations
- If malicious, we can write executable code into this space, set return address to jump into our code…



Example of call stack within the call to the function `foo()`

Arbitrary Code Execution

- Buffer overflows in network code are the primary source of security problems
  - If you write network code in C, but *very* careful to check all array bounds
  - If your code can be crashed by network traffic, it probably has an exploitable buffer overflow
- http://insecure.org/stf/smashstack.html

Wrap Up

Examination and Revision

- Exam is worth 80% of course mark
  - Duration: 1.5 hours
  - Rubric: answer all 3 questions
  - Copies of past exam papers are on Moodle

- No revision lecture – email me with any questions

Networked Systems in Level 4

- Three taught modules cover networked systems:
  - Advanced Networking and Communications 4
  - Distributed Algorithms and Systems 4
  - Wireless Sensor Networks 4/M
- Individual projects in networked systems:
  - Look for projects supervised by members of the Embedded, Networked, and Distributed Systems research group
  - Talk to us if you're interested in networking-related projects – we generally have more project ideas than proposed, and can often suggest something that fits with your interests
  - Level 4 projects in this area can lead to MSci/PhD work, if interested

Questions?