# Types and Traits

Advanced Systems Programming (H) 2020-2021 – Laboratory Exercise 2
Dr Colin Perkins, School of Computing Science, University of Glasgow

## 1 Introduction

The Advanced Systems Programming (H) course uses the Rust programming language (`https://rust-lang.org/`) to illustrate several advanced topics in systems programming. You're expected to learn the basics of programming in Rust as part of this course. This exercise is a further introduction to the Rust programming language. **This is a formative exercise and is not assessed.**

## 2 Types, data structures, and traits in Rust

Some key features of the Rust programming language are those that allow it to express more advanced types and data structures, and those that support behavioural abstraction. This includes structure types, and the ability to implement methods on data structures; enumerated types and pattern matching, to express alternative types for an object; and generics, type parameters, and traits that allow abstraction over different types and behaviours.

### 2.1 Structure types and methods

Structure types describe heterogeneous collections of data. A `struct` has a name and comprises a set of zero or more fields. The fields may have names, as in the example below, or can be unnamed. If the fields are unnamed, the `struct` is used similarly to a tuple, but has a type name that makes it easier to reference in some contexts. It is possible for a `struct` to have no fields, in which case it takes up no space; such empty structures can be useful as marker types to describe that some condition is met.

An example of a `struct` might be:

```
struct Rectangle {
    width: u32,
    height: u32
}
```

In addition to containing data, structures can have associated methods. These are specified in an `impl` block for the `struct`, and define functions that may be called on instances of that `struct`. For example, an `area()` method can be added to the `Rectangle` structure defined above in the following way:

```
impl Rectangle {
    fn area(&self) -> u32 {
        self.width * self.height
    }
}

fn main() {
    let rect = Rectangle { width: 30, height: 50 };

    println!("Area of rectangle is {}", rect.area());
}
```

Methods implemented on a `struct` take `self` as an explicit parameter. This is typically done as a reference (`&self`); we'll discuss the self type of structures in more detail in Lecture 4. Fields are accessed with an explicit `self`, as in Python. Rust is not an object oriented language, but a `struct` with associated methods can be used to fill a similar role to an object in many cases.

Read Chapter 5 of the online Rust book (`https://doc.rust-lang.org/book/ch05-00-structs.html`) and work through the examples. It describes how structures and methods work in Rust. There is some discussion of ownership of `struct` data in the book; we will discuss how Rust manages ownership of data in more detail in Lecture 5.

## 2.2 Enumerated types and pattern matching

Structures represent a single type that contains multiple fields of data. By contrast, an enumeration (`enum`) can be used to represent data that has several different variants. An `enum` type has a name, and comprises several different variants. Each variant is its own type, and can contain fields much like a `struct`. When instantiated, an `enum` has type matching *one* of the variants. The example below describes a `RoughTime` enumeration with three variant types: `InThePast`, `JustNow`, and `InTheFuture`, two of which have fields associated with them:

```
enum RoughTime {
    InThePast(TimeUnit, u32),
    JustNow,
    InTheFuture(TimeUnit, u32)
}

let when = RoughTime::InThePast(TimeUnit::Years, 4*20 + 7);
```

The concept of *pattern matching* can be used to select between values, including different variants of enumerations. In its simplest form, a `match` expression in Rust work much like a `switch` statement in C or Java, but it can generalise to work on different types of data and to bind to associated fields in that data. For example, it's possible to match against variants of the `RoughTime` enumeration define above in the following way:

```
match rt {
  RoughTime::InThePast(units, count) => format!("{} {} ago", count, units.plural()),
  RoughTime::JustNow => format!("just now"),
  RoughTime::InTheFuture(units, count) => format!("{} {} from now", count, units.plural())
}
```

Read chapter 6 of the online Rust book (`https://doc.rust-lang.org/book/ch06-00-enums.html`). That chapter describes enumerated types and pattern matching. Work through the examples. Pay particular attention to the use of `Option<T>` as a way to signal functions that return optional values, rather than passing back a potentially null pointer.

## 2.3 Type parameters and traits

Rust provides three ways of writing code that is generic across different types. The first is to define an `enum` to encapsulate the possible alternatives and pattern match on the variants, as described in Section 2.2 of this handout. Second, if the types are not known, it is possible to write generic data structures and functions that accept type parameters, abstracting across unknown data types. For example, a library that deals with coordinates and geometry (perhaps a graphics library) might need to deal with *points* in the abstract, independent on the underlying type used to specify x- and y-coordinates. Such a library could define a `Point<T>` type, with a *type parameter* `T` that's specified when a variable of that type is instantiated to define the concrete type of the fields:

```
struct Point<T> {
    x: T,
    y: T,
}

fn main() {
    let int_point = Point::<u32> { x: 5,   y: 10  };
    let flt_point = Point::<f64> { x: 1.0, y: 4.0 };
}
```

The syntax `::<T>`, known as the *turbo fish*, allows you to specify the type parameter, `T`, when instantiating a `Point` structure. If it is omitted, e.g., `Point {x:5, y:10}`, the compiler will try to infer the type of the type parameter.

Finally, it is possible to define *traits* to abstract across different types that offer the same behaviour. A `trait` definition specifies the name of the trait, along with a set of prototypes for methods that instances of the trait must implement, but provides no body for those methods. For example, a trait `Area` that defines a single method, `area()`, can be expressed as follows:

```
trait Area {
    fn area(&self) -> u32;
}
```

This is similar to an interface definition in a language such as Java. It indicates that types that implement the trait must provide implementations of the specified functions. Such implementations are provided by an `impl` block specifying the trait name and type for which it's implemented. For example, the `Area` trait mentioned above could be implemented as follows:

```
impl Area for Rectangle {
    fn area(&self) -> u32 {
        self.width * self.height
    }
}
```

Traits are often used to solve the same types of problems that subclasses solve in object oriented languages, or that duck-typing solves in dynamic languages such as Python. They make it possible to implement code that works with any type that implements a particular set of methods. This is done by specifying a trait bound as a type parameter to a function. For example, the `notify()` function below can be instantiated for any type `T`, where the definition of the type parameter (given in angle brackets) indicates that `T` implements the trait `Summary`:

```
trait Summary {
    fn summarize(&self) -> String;
}

fn notify<T: Summary>(item: T) {
    println!("Breaking news! {}", item.summarize());
}
```

Read Sections 10.1 and 10.2 of the Rust book (`https://doc.rust-lang.org/book/ch10-00-generics.html`) and work through the examples. The final part of the chapter, on "Validating References with Lifetimes", relates to the Rust ownership and borrowing rules that we'll discuss in Lecture 5, and shouldn't be attempted at this time.


## 3 Type-driven Development

One of the benefits of using a programming languages with an expressive type system is that it becomes possible to develop an effective model of the problem domain using the type system.

At its most basic, this can simply represent the different types of object present and the legal operations that can be performed on those objects. More expressive languages can also encode state machines and behaviours, allowing the compiler to help check solutions for consistency. This introduces some up-front design and modelling costs, but reduces later debugging effort.

For example, consider the POP3 email retrieval protocol, described by the IETF in RFC1939.[1] This has a state machine that is structured as follows:

[1] `https://tools.ietf.org/html/rfc1939`




When not connected to the email server, the only possible operation is to connect to the server, putting the system into the AUTHORIZATION state. Once connected in the AUTHORIZATION state, the user can login by sending a username and password. If these are correct, the system enters the TRANSACTION state; otherwise it returns to AUTHORIZATION. In the TRANSACTION state, the user can list, retrieve, or delete email messages, or can quit. Quitting moves the system into the UPDATE state, where any changes made are committed and a status code returned, before the system disconnects from the email server.

Read RFC 1939 and study the above state-transition diagram, to get a high-level understanding of the behaviour of the POP3 protocol and to practice reading protocol specifications. Sketch out a rough type-level design for a POP3 server implementation. This should use Rust `structs` to represent the various states, with methods on those structures representing operations and state transitions. Think about how the Rust ownership rules help to enforce that operations are performed only in the correct order and in the correct state. Consider what types might be needed, in addition to those representing the states.

**This is a formative exercise and is not assessed.** You do not need to submit your solution. An outline solution will be discussed as part of Lecture 4.

- + -